

Ring / Multidrop Fibre Converter RS-232

ODW-720-F2 EX

- Numerous fibre configuration options
 - Up to 120 km distance
 - BiDi support (single fibre)
 - Multimode and singlemode SFPs in single ring
- Designed for use in industrial applications
 - Dual 10 V to 60 VDC power input
 - 500,000h MTBF according to MIL HDBK-217K
 - ATEX Zone 2 – Ex II 3 G Ex nA IIC T4 Gc
- Unique solutions for serial RS-232 protocols
 - Data rates to 250 kbit/s
 - Up to 12 data bits
 - Dual channel for status (RTS/CTS) transmission
- Simple to use and install
 - Transparent to any data rate
 - Comprehensive diagnostic LEDs
 - Compact housing with integral DIN rail clip



EN 61000-6-2
Industrial Immunity

EN 61000-6-3
Residential Emission

EN 61000-6-4
Industrial Emission

EN 50121-4
Railway Trackside

The ODW-720-F2 EX has been designed to allow RS-232 protocols to be transmitted point-to-point over a fibre optic link. The design allows the use of a range of Westermo verified SFP (Small Form Pluggable) transceivers which can provide solutions with, for example, only a single fibre or distances up to 120 km.

This unit has been designed for industrial use where the requirement is for a long and reliable service life, in a harsh environment. To ensure this reliable operation we manufacture using the highest quality components.

The ODW-720 draws on Westermo's many years of knowledge of serial protocols and can even transmit the RTS/CTS hardware controls if required.


The ODW is simple to install, being small, with a simple integral DIN rail clip. The unit is totally transparent to any data rate so no configuration is needed. The comprehensive LEDs provide a quick and easy way of detecting any network problems that may be encountered.

Ordering Information

Art.no	Description
3651-3722	ODW-720-F2 EX
3125-0001	PS-30, Power supply, DIN mounted (Accessories)

Specifications ODW-720-F2 EX

Dimensional drawing



Dimension W x H x D 35 x 121 x 119 mm (1.37 x 4.76 x 4.68 in)
Weight 0.26 kg
Degree of protection IP 21

Power	
Operating voltage	10 to 60 VDC and 20 to 30 VAC
Rated current	400 mA @ 12 V 200 mA @ 24 V 100 mA @ 48 V

Interfaces	
Status	1 x Detachable screw terminal
RS-232	1 x 300 bit/s – 250 kbit/s
FX (Fibre)	2 x LC Duplex or LC Simplex

Temperature	
Operating	–40 to +60°C (–40 to +140°F)
Storage & Transport	–40 to +60°C (–40 to +140°F)

Agency approvals and standards compliance	
EMC	EN 61000-6-1, Immunity residential environments
	EN 61000-6-2, Immunity industrial environments
	EN 61000-6-3, Emission residential environments
	EN 61000-6-4, Emission industrial environments
	EN 55022, Emission IT equipment, class A
	EN 55024, Immunity IT equipment
	FCC part 15 Class A
	EN 50121-4, Railway signalling and telecommunications apparatus
ATEX	IEC 62236-4, Railway signalling and telecommunications apparatus
	EN 60079-0 and EN 60079-15