

Intelligent Optical Link Mapper (iOLM)

AUTOMATED, EXPERT-LEVEL SINGLEMODE FIBER TESTING



Available on:

- > FTB-720 LAN/WAN test module
- > FTB-730 FTTx/PON test module

POWERED BY

LINK-AWARE™
TECHNOLOGY

Patent protection applies to the intelligent Optical Link Mapper, including its proprietary measurement software. EXFO's Universal Interface is protected by US patent 6,612,750.

Using automated multipulse acquisitions and advanced algorithms, the iOLM is an OTDR-based application that delivers detailed information on every element on the link, in a single button operation—providing maximum intelligence and simplicity for expert-level link characterization.

KEY FEATURES

Self-setting unit

Link-Aware technology

Optical Link View

Prompt diagnosis

In-line optical power meter

OTDR trace file generation (.sor)

CHOOSE THE PERFECT FIT

The iOLM is offered as a stand-alone application or as a field-upgradable software option with the OTDR application.

FTB-720 LAN/WAN test module

Dynamic range up to 36 dB

Point-to-point testing of short access links

Multimode and singlemode testing

FTB-730 FTTx/PON test module

Dynamic range up to 39 dB

Ideal for deploying FTTH and point-to-point (access and metro) networks

End-to-end PON characterization (splitter configuration up to 1 x 128)

PLATFORM COMPATIBILITY



FTB-1
One-module platform
for dedicated applications

EXFO | Connect

EXFO

Assessing
Next-Gen Networks

EXFO Connect

EXFO | Connect

AUTOMATED ASSET MANAGEMENT. PUSH TEST DATA IN THE CLOUD. GET CONNECTED.

EXFO Connect stores and pushes test equipment and test data content automatically in the cloud, allowing you to streamline test operation from build-out to maintenance.

REVOLUTIONIZING SINGLE-ENDED FIBER DEPLOYMENTS



Link-Aware™ Technology

Let it optimize the test run

With one click, the unit automatically performs link recognition, sets the optimal parameters and launches multiple acquisitions and multiple analyses—at multiple wavelengths—consolidating the results obtained for every link section and every network element. Get accurate information right away on each link element and export it to a single report.



Self-Setting Unit

Let it be the expert

Powered by Link-Aware technology, the iOLM self-manages the setting of all test parameters—ready-to-use intelligence that dramatically shortens the learning curve. Minimize training, avoid test misconfiguration, and facilitate your technicians' transition from copper to fiber.



Optical Link View

Let it crunch the data

Leaving behind complex OTDR traces, the simplified link mapper provides a straightforward view of the fiber under test, with clear icons and pass/fail verdicts. Get actual results: end-to-end visual assessment of your link, complete with event characterization and fiber status.



Prompt Diagnosis

Let it show you the way

Loaded with countless algorithms and a database of potential network failures, the iOLM guides you through your network's problem-solving process. Say goodbye to trace misinterpretation, and ensure that all your technicians—not just your most experienced ones—can efficiently fix network issues right on the spot.



In-Line Optical Power Meter (available with FTB-730 only)

Let it fast-track troubleshooting

Connect, check power readings, get a link map and find the fault—all in one click and without disconnecting the fiber. Gear up for lightning-fast troubleshooting.



OTDR Trace File Generation

Let it fit your existing test filing requirements

The iOLM can generate a universal and enhanced Bellcore format (.sor) OTDR trace to comply with your existing reporting and post-processing requirements. This OTDR trace integrates all the additional information gathered by the iOLM, providing more complete results.

Mandatory: Angled-Polished (APC) Connectors

Like any OTDR, the iOLM will be impacted by strong reflections at the unit's port. To ensure low reflections and maintain measurement accuracy, the iOLM singlemode port must be used with APC connectors. Another advantage of using APC connectors is their ability to handle harsher conditions without becoming highly reflective while maintaining the unit's performance.

In the case of UPC connectors, they are prone to be highly reflective if contaminated, worn or damaged. This will affect the measurement and will lead to premature connector replacement. Although testing a UPC network does not require a UPC unit, using an APC/UPC test jumper (included with the iOLM) or a launch fiber (SPSB) ensures compatibility.

Recommended Test Method

EXFO recommends using a 150-meter launch cable (SPSB) to exclude the loss of the iOLM's connector or to allow UPC network testing. It will also extend the instrument's connector life by reducing the number of matings—ultimately improving the cost of ownership.



GENERAL SPECIFICATIONS		
Module	FTB-720	FTB-730
Size (H x W x D)	130 mm x 36 mm x 252 mm (5 1/8 in x 1 7/16 in x 9 15/16 in)	130 mm x 36 mm x 252 mm (5 1/8 in x 1 7/16 in x 9 15/16 in)
Weight	0.65 kg (1.4 lb)	0.65 kg (1.4 lb)

LASER SAFETY	
21 CFR 1040.10 AND IEC 60825-1:2007 CLASS 1M WITHOUT VFL OPTION CLASS 3R WITH VFL OPTION	<p>IEC 60825-1:2007 21 CFR 1040.10 INVISIBLE LASER RADIATION DO NOT VIEW DIRECTLY WITH OPTICAL INSTRUMENTS CLASS 1M LASER PRODUCT λ: 800-1000 nm, P_{AV} ≤ 1 mW, P_{EM} ≤ 500 mW λ: 1200-1400 nm, P_{AV} ≤ 20 mW, P_{EM} ≤ 250 mW λ: 1200-1700 nm, P_{AV} ≤ 20 mW, P_{EM} ≤ 250 mW 0513 372</p>
	<p>IEC 60825-1:2007 21 CFR 1040.10 VISIBLE LASER RADIATION AVOID DIRECT EYE EXPOSURE CLASS 3R LASER PRODUCT λ: 650 - 670 nm P_{OUT} maximum < 5mW (into free space)</p>

ORDERING INFORMATION

Multimode and Singlemode Access and LAN/WAN OTDR

FTB-720-XX-XX-XX-XX-XX

Model

FTB-720-000-04B = OTDR with filtered 1625 nm port
 FTB-720-023B-04B = OTDR 1310/1550 nm with filtered 1625 nm port
 FTB-720-23B = OTDR 1310/1550 nm
 FTB-720-12CD = OTDR 850/1300 nm
 FTB-720-12CD-23B = OTDR 850/1300 nm, 1310/1550 nm

Multimode Connector

EI-EUI-28 = UPC/DIN 47256
 EI-EUI-76 = UPC/HMS-10/AG
 EI-EUI-89 = UPC/FC narrow key
 EI-EUI-90 = UPC/ST
 EI-EUI-91 = UPC/SC
 EI-EUI-95 = UPC/E-2000

Software Options^b

00 = Without software option
 AD = Auto diagnostic (macroband detection, pass/fail and fault finder)
 EC = Event characterization (bidirectional analysis and Template mode)

Base Software

OTDR = Enables the OTDR application only
 iOLM^a = Enables the iOLM application only
 Oi^a = Enables iOLM and OTDR applications

Singlemode Connector

EA-EUI-28 = APC/DIN 47256
 EA-EUI-89 = APC/FC narrow key
 EA-EUI-91 = APC/SC
 EA-EUI-95 = APC/E-2000
 EI connectors = See note below

Example: FTB-720-23B-04B-OTDR-EI-EUI-89-EA-EUI-89

Singlemode (PON FTTx/MDU) OTDR for FTB-1 Platform

FTB-730-XX-XX-XX-XX-XX

Model

Dual-Wavelength

FTB-730-23B = SM OTDR module, 1310/1550 nm (9/125 µm)
 FTB-730-34B = SM OTDR module, 1550/1625 nm (9/125 µm)

Triple-Wavelength

FTB-730-236B = SM OTDR module, 1310/1490/1550 nm (9/125 µm)

SM Live Port

FTB-730-23B-04B = SM and SM live OTDR module, 1310/1550 and 1625 nm live port including in-line broadband power meter
 FTB-730-000-04B = SM live OTDR with 1625 nm live port (9/125 µm) including in-line broadband power meter
 FTB-730-000-08B = SM live OTDR with 1650 nm live filtered port (9/125 µm)

Connector

EA-EUI-28 = APC/DIN 47256
 EA-EUI-89 = APC/FC narrow key
 EA-EUI-91 = APC/SC
 EA-EUI-95 = APC/E-2000
 EI connectors = See note below

Base Software

OTDR = Enables the OTDR application only
 iOLM = Enables the iOLM application only
 Oi = Enables iOLM and OTDR applications

OPM Option^c

OPM = One broadband channel included
 OPM2 = Dual channel 1490/1550 nm

Software Options^b

00 = Without software option, OTDR application
 AD = Automatic diagnosis (macroband detection, pass/fail and fault finder) and linear view
 EC = Event characterization (bidirectional analysis and Template mode)

Example: FTB-730-023B-04B-OPM-iOLM-EA-EUI-89

SPSB-XX-XX

Model

Dual-Wavelength

SPSB-B-150 = Soft pulse suppressor bag, singlemode fiber 9/125 µm, 150 m

Connector

58 = FC/APC narrow key
 88 = SC/APC narrow key
 89 = FC/UPC
 90 = ST/UPC
 91 = SC/UPC
 95 = E2000/UPC
 96 = E2000/APC
 101 = LC/UPC^d
 104 = LC/APC^d

Notes

- The iOLM software is available on singlemode port only. FTB-720-12CD-23B must be ordered with Oi option to enable iOLM on the singlemode port.
- Available only with OTDR base software.
- Available only with FTB-730-000-04B and FTB-730-23B-04B.
- LC connectors are not available for first connector.

Example: SPSB-B-150-58-101

EI CONNECTORS



To maximize the performance of your OTDR, EXFO recommends using APC connectors. These connectors generate lower reflectance, which is a critical parameter that affects performance, particularly dead zones. APC connectors provide better performances than UPC connectors, thereby improving testing efficiency.

Note: UPC connectors are also available, simply replace EA-XX by EI-XX in the ordering part number. Additional connectors available are the EI-EUI-76 (UPC/HMS-10/AG) and EI-EUI-90 (UPC/ST).

EXFO Corporate Headquarters > 400 Godin Avenue, Quebec City (Quebec) G1M 2K2 CANADA | Tel.: +1 418 683-0211 | Fax: +1 418 683-2170 | info@EXFO.com

Toll-free: +1 800 663-3936 (USA and Canada) | www.EXFO.com

EXFO America	3400 Waterview Parkway, Suite 100	Richardson, TX 75080 USA	Tel.: +1 972 761-9271	Fax: +1 972 761-9067
EXFO Asia	100 Beach Road, #22-01/03 Shaw Tower	SINGAPORE 189702	Tel.: +65 6333 8241	Fax: +65 6333 8242
EXFO China	36 North, 3 rd Ring Road East, Dongcheng District Room 1207, Tower C, Global Trade Center	Beijing 100013 P.R. CHINA	Tel.: + 86 10 5825 7755	Fax: +86 10 5825 7722
EXFO Europe	Omega Enterprise Park, Electron Way	Chandlers Ford, Hampshire S053 4SE ENGLAND	Tel.: +44 23 8024 6810	Fax: +44 23 8024 6801
EXFO Finland	Elektronikkatie 2	FI-90590 Oulu, FINLAND	Tel.: +358 (0)403 010 300	Fax: +358 (0)8 564 5203
EXFO Service Assurance	270 Billerica Road	Chelmsford, MA 01824 USA	Tel.: +1 978 367-5600	Fax: +1 978 367-5700

EXFO is certified ISO 9001 and attests to the quality of these products. This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. EXFO has made every effort to ensure that the information contained in this specification sheet is accurate. However, we accept no responsibility for any errors or omissions, and we reserve the right to modify design, characteristics and products at any time without obligation. Units of measurement in this document conform to SI standards and practices. In addition, all of EXFO's manufactured products are compliant with the European Union's WEEE directive. For more information, please visit www.EXFO.com/recycle. Contact EXFO for prices and availability or to obtain the phone number of your local EXFO distributor.

For the most recent version of this spec sheet, please go to the EXFO website at www.EXFO.com/specs.

In case of discrepancy, the Web version takes precedence over any printed literature.