

FLS-5834A

NETWORK TESTING—OPTICAL



- High-power super LED (SLED)
- Modulated for chromatic dispersion measurement
- Polarized for PMD measurement
- Broadband spectral range

EXFO's FLS-5834A CD/PMD Analyzer Source is a modulated, polarized, high-power SLED. Thanks to its high power density, you can use it as a broadband source for DWDM channel and component testing.

High Modulation

The FLS-5834A's high modulation makes it a perfect complement to the FTB-5800 Chromatic Dispersion Analyzer, whose technology is based on the phase-shift method. This first-class duo lets you run chromatic dispersion (CD) measurements through amplifiers such as EDFAs, providing the highest accuracy in field CD testing.

High Degree of Polarization

When you need a broadband, highly polarized source for measuring PMD, turn to the FLS-5834A. Test PMD through EDFAs by combining the FLS-5834A with the patent-design breakthrough technology of the FTB-5500B PMD Analyzer.

SPECIFICATIONS ^a

Center wavelength (nm)	1580 ±20
Output power (dBm)	7
Peak spectral density (dBm/nm)	> -12.5
Power stability (15 minutes) (dB)	< 0.075
Modulation frequency (MHz)	100

GENERAL SPECIFICATIONS

Temperature		
operating	0 °C to 40 °C	(32 °F to 104 °F)
storing	-20 °C to 50 °C	(-4 °F to 122 °F)
Relative humidity (non-condensing)	0 % to 90 %	
Size (H x W x D)	117 mm x 222 mm x 333 mm	(4 5/8 in x 8 3/4 in x 13 1/8 in)
Weight (without transceivers)	3.2 kg	(7.1 lb)

NOTES

a. Typical

ORDERING INFORMATION

MODULE

FLS-5834A-XX

Model

FLS-5834A = 1550 nm and 1625 nm

Connector

EI-EUI-28 = UPC/DIN 47256
 EI-EUI-76 = UPC/HMS-10/AG (EI only)
 EI-EUI-89 = UPC/FC narrow key
 EI-EUI-90 = UPC/ST (EI only)
 EI-EUI-91 = UPC/SC
 EI-EUI-95 = UPC/E-2000
 EA-EUI-28 = APC/DIN 47256
 EA-EUI-89 = APC/FC narrow key
 EA-EUI-91 = APC/SC
 EA-EUI-95 = APC/E-2000

Example: FLS-5834A-EI-EUI-89

LED SAFETY

IEC 60825-1:2001 CLASS 1M LED PRODUCT

EXFO Corporate Headquarters > 400 Godin Avenue, Quebec City (Quebec) G1M 2K2 CANADA | Tel.: 1 418 683-0211 | Fax: 1 418 683-2170 | info@EXFO.com

Toll-free: 1 800 663-3936 (USA and Canada) | www.EXFO.com

EXFO America	3701 Plano Parkway, Suite 160 Plano, TX 75075 USA	Tel.: 1 800 663-3936	Fax: 1 972 836-0164
EXFO Europe	Omega Enterprise Park, Electron Way Chandlers Ford, Hampshire S053 4SE ENGLAND	Tel.: +44 2380 246810	Fax: +44 2380 246801
EXFO Asia	151 Chin Swee Road, #03-29 Manhattan House SINGAPORE 169876	Tel.: +65 6333 8241	Fax: +65 6333 8242
EXFO China	No.88 Fuhua, First Road Central Tower, Room 801, Futian District Beijing New Century Hotel Office Tower, Room 1754-1755 No. 6 Southern Capital Gym Road	Shenzhen 518048, CHINA Beijing 100044 P. R. CHINA	Tel.: +86 (755) 8203 2300 Tel.: +86 (10) 6849 2738 Fax: +86 (755) 8203 2306 Fax: +86 (10) 6849 2662

EXFO is certified ISO 9001 and attests to the quality of these products. This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. EXFO has made every effort to ensure that the information contained in this specification sheet is accurate. All of EXFO's manufactured products are compliant with the European Union's WEEE directive. For more information, please visit www.EXFO.com/recycle. However, we accept no responsibility for any errors or omissions, and we reserve the right to modify design, characteristics and products at any time without obligation. Units of measurement in this document conform to SI standards and practices. Contact EXFO for prices and availability or to obtain the phone number of your local EXFO distributor.

For the most recent version of this spec sheet, please go to the EXFO website at <http://www.EXFO.com/specs>

In case of discrepancy, the Web version takes precedence over any printed literature.